CASALI S.p.A. - z.i. C.I.A.F. 60015 Castelferretti (AN) - ITALY
tel. +39 071 9162095 - fax +39 071 9162098
www.casaligroup.it info@casaligroup.it

DECLARATION OF PERFORMANCE

N° DOP F03069

1. Unique identification code of the product-type:

F03069 - SAT ITALICA 10 4 MM HSP POL GREY MINERAL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See roll label

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Flexible bitumen sheet for waterproofing:

Reinforced bitumen sheets for roof waterproofing

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

CASALI SPA Zona Industriale C.I.A.F. 60015 Castelferretti Falconara Marittima, Ancona
www.casaligroup.it

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

- Reinforced bitumen sheets for roof waterproofing. System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
EN 13707

The notified body SGS (n° 1381) on the basis of the control on production issued the conformity certificate of Factory Production Control n° 1381-CPR-376 founded on the following elements:
- Initial inspection of factory and of FPC;
- Continuous surveillance, assessment and approval of FPC.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

CASALI S.p.A. - z.i. C.I.A.F. 60015 Castelferretti (AN) - ITALY
tel. +39 071 9162095 - fax +39 071 9162098
www.casaligroup.it info@casaligroup.it

9. Declared performance

Essential characteristics	Unit	Performance	Harmonised technical specification
External fire performance	Class	F roof	EN 13707:2004 + A2:2009
Reaction to fire	Class	E	
Watertightness	60 KPa	Pass	
Tensile properties			
Tensile properties:maximum tensile force L/T	N/50 mm	850 / 650 (±20%)	
Tensile properties:elongation L/T	%	40 / 40 (±15)	
Resistance to root penetration	Statement	NPD	
Resistance to static loading	kg	>= 20	
Resistance to impact	mm	>= 1250	
Resistance to tearing (nail shank) L/T	N	170 / 170 (±30%)	
Joint strenght			
Peel resistance of joints	N/50 mm	NPD	
Shear resistance of joints	N/50 mm	750/550	
Durability after thermal aging			
Flexibility at low temperature after heat aging	°C	<= NPD	
Flow resistance at elevated temperature after heat aging	°C	>= 120	
Artificial aging by combination of UV radiation and water	Statement	NPD	
Flexibility at low temperature	°C	<= -10	
Dangerous substances		See note 1	

L = Longitudinal ; T = Transversal; NPD=No Peformance Determined *Tested on system

Note 1: National rules on hazardous substances may require verification and a declaration for release, and sometimes on the contents, when the construction products covered by this standard are placed on those markets. The product does not contain absestos or tar constituents.

10. The performances of the product identified in points 1 and 2 are in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Falconara M. , 01/08/2026

Casali S.p.A.
Quality Assurance Manager
Ing. Marco Compagnucci

